

fitt captive grey



适用于淋浴和洗手池灰水排放的理想管道。

FITT Captive Grey采用特殊吸味配方制成，柔韧性好，耐压，耐低温。

结构: 带镀锌钢螺旋的PVC管。

使用温度: -10°C / +65°C

- 良好的柔韧性。
- 良好的抗压强度。

Hose ideal for the flow of grey shower and sink water.

Made with a special odour-absorbing formulation, FITT Captive Grey is flexible, crushing and low temperature resistant.

Structure: PVC hose with galvanised steel spiral.

Temperature of use: -10°C / +65°C

- Good flexibility.
- Good crushing resistance.



符合REACH¹
标准
REACH¹
compliant



符合RoHS²
标准
RoHS²
compliant



无IPA³
PAH³
free



无邻苯二甲酸盐⁴
含量<0.1%
Phthalate free⁴
formulation <0.1%

欧洲专利号: 102018000006290。
正在申请欧洲专利。

Italian Patent N. 102018000006290.
European patent pending.

FITT CAPTIVE GREY

标记 | Marking: FITT CAPTIVE GREY Øxx - MADE IN ITALY - 10 YEARS WARRANTY

英寸 Inches [inc]	内径 Ø internal [mm]	外径 Ø external [mm]	厚度 Thickness [mm]	工作压力 Working pressure [bar]	爆破压力 Bursting pressure [bar]	真空度 Vacuum [mH ₂ O]	弯曲半径 Bending radius [mm]	长度 Length [m]	每托盘件数 Pieces per pallet [pcs]	托盘尺寸 Pallet dimension [cm]
-	16	22,6	3,3	7	21	9	40	30	45	120x120
-	18	25	3,5	7	21	9	40	30	36	120x120
-	20	27,2	3,6	6	18	9	40	30	32	120x120
1"	25	33	4	5	15	9	50	30	16	120x120
-	30	38	4	4	12	9	60	30	14	120x120
-	32	40,2	4,1	4	12	9	70	30	9	80x120
-	35	43,4	4,2	3	9	9	70	30	8	80x120
1 1/2"	38	47	4,5	3	9	9	80	30	6	80x120
-	40	49	4,5	3	9	9	80	30	6	80x120
-	50	60,4	5,2	2,5	7,5	8	110	30	5	120x120
2"	51	61,4	5,2	2,5	7,5	8	110	30	5	120x120

时的爆破压力和工作压力23°C | Working and Bursting pressure at 23°C

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1.符合REACH法规 (EC) 第1907/2006号 / 2.符合RoHS条例 / 3.符合AFPS GS 2019:01 IPA法规 - 第2类 / 4.无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)