

fitt cristallo extra



食品行业、工业生产厂房和水疗中心低压液体输送的理想软管。

FITT Cristallo Extra通过食品物质认证,可输送酒精含量高达50%vol的物质,同时也适用于压力输送空气和冷却水。在热成型工艺中,它也适用于树脂的低压输送。

结构:非增强型PVC软管。

使用温度:-20°C / +60°C

- 良好的柔韧性。

Hose ideal for low the pressure flow of liquids in the food sector, for industrial production plants and spas.

Certified for the passage of liquid foods with alcohol content up to 50% vol, FITT Cristallo Extra is also ideal for the low-pressure flow of air and cooling water. It is also suitable for the passage of resin in low pressure, in thermoforming processes.

Structure: Non-reinforced PVC hose.

Temperature of use: -20°C / +60°C

- Good flexibility.



符合REACH¹
标准
REACH¹
compliant

符合RoHS²
标准
RoHS²
compliant

无IPA³
PAH³
free

无邻苯二甲酸盐⁴
含量<0.1%
Phthalate free⁴
formulation <0.1%



MOCA - 符合欧盟第10/2011号法规
(模拟物A-B-C-D1)
FDA批准CFR 21 - 175.300和177.1210。

FCM - Compliant with European Regulation
10/2011 for Simulants A-B-C-D1.
Compliant with FDA CFR 21 - 175.300 and
177.1210.

FITT CRISTALLO EXTRA

标记 | Marking: FITT CRISTALLO EXTRA DlxDE Reg.(EU) 10/2011 A-B-C-D1 FDA CFR 21 175.300 - PHTHALATE FREE - MADE IN ITALY

内径 Ø internal [mm]	外径 Ø external [mm]	厚度 Thickness [mm]	工作压力 Working pressure* [bar]	爆破压力 Bursting pressure [bar]	长度 Length [m]	标称重量 Weight per meter [g/m]	每托盘件数 Pieces per pallet [pcs]	尺寸托盘 Pallet dimension [cm]
2	4	1	11	33	100	12	200	80x120
3	5	1	7	21	100	15	150	80x120
3	6	1.5	11	33	100	26	120	80x120
4	6	1	5	15	50	19	150	80x120
4	6	1	5	15	100	19	150	80x120
4	7	1.5	8	24	50	32	96	80x120
4	7	1.5	8	24	100	32	110	80x120
5	7	1	4	12	100	23	64	80x120
5	7	1	4	12	200	23	60	80x120
5	8	1.5	6	18	5	37	648	80x120
5	8	1.5	6	18	50	37	96	80x120
5	8	1.5	6	18	100	37	60	80x120
5	9	2	9	27	100	54	48	80x120
6	8	1	4	12	100	27	66	80x120
6	8	1	4	12	50	27	96	80x120
6	9	1.5	6	18	5	43	576	80x120
6	9	1.5	6	18	25	43	195	80x120
6	9	1.5	6	18	50	43	96	80x120
6	9	1.5	6	18	100	43	60	80x120
6	10	2	8	24	50	62	96	80x120
6	10	2	8	24	100	62	48	80x120
7	9	1	3	9	50	30	96	80x120
7	10	1.5	5	15	5	49	504	80x120
7	10	1.5	5	15	50	49	64	80x120
7	10	1.5	5	15	100	49	60	80x120
7	11	2	7	21	100	68	42	80x120

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1.符合REACH法规 (EC) 第1907/2006号 / 2.符合RoHS条例 / 3.符合AFPS GS 2019:01 IPA法规 - 第2类 / 4.无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)