

fitt lightflex



工业和船舶用软管, 是抽吸和通风的理想选择。

FITT Lightflex软管柔韧耐用, 适用于低温抽吸烟尘和通风。

结构: PVC螺旋管, 配有抗冲击的硬质PVC增强螺旋。
使用温度: -15°C / +60°C

- 高柔韧性。
- 高耐用性。

Hose for industrial use and in the nautical sector, ideal for suction and ventilation systems.

Flexible and durable, FITT Lightflex is suitable for low-temperature smoke and dust extraction and ventilation.

Structure: PVC spiral hose with reinforcement spiral in rigid shock-resistant PVC.
Temperature of use: -15°C / +60°C

- High flexibility.
- High durability.



符合REACH¹
标准
REACH¹
compliant



符合RoHS²
标准
RoHS²
compliant



无IPA³
PAH³
free



无邻苯二甲酸盐⁴
含量<0.1%
Phthalate free⁴
formulation <0.1%

FITT LIGHTFLEX

标记 | Marking: FITT LIGHTFLEX Øxx - PHTHALATE FREE - MADE IN ITALY

英寸 Inches [inc]	内径 Ø internal [mm]	外径 Ø external [mm]	厚度 Thickness [mm]	真空度 Vacuum [mH ₂ O]	弯曲半径 Bending radius [mm]	长度 Length [m]	标称重量 Weight per meter [g/m]	每托盘件数 Pieces per pallet [pcs]	托盘尺寸 Pallet dimension [cm]
3/4"	19	23,8	2,4	3	19	25	110	30	80x120
3/4"	19	23,8	2,4	3	19	50	110	20	80x120
1"	25	30	2,5	3	25	25	140	18	80x120
1"	25	30	2,5	3	25	50	140	20	120x120
-	30	35,4	2,7	3	30	25	200	28	120x120
-	30	35,4	2,7	3	30	50	200	16	120x120
1 1/4"	32	37,4	2,7	3	32	50	220	12	120x120
-	35	40,6	2,8	3	35	25	240	20	120x120
-	35	40,6	2,8	3	35	50	240	6	80x160
1 1/2"	38	44,2	3,1	3	38	25	270	8	80x120
1 1/2"	38	44,2	3,1	3	38	50	270	8	80x160
-	40	46,4	3,2	3	40	25	280	16	120x120
-	40	46,4	3,2	3	40	50	280	6	80x160
1 3/4"	45	51,4	3,2	3	45	50	360	4	80x160
2"	50	57,2	3,6	3	50	25	450	6	80x120
2"	50	57,2	3,6	3	50	50	450	3	120x120
-	60	68,4	4,2	2	60	25	540	5	120x120
-	60	68,4	4,2	2	60	50	540	3	120x120

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1.符合REACH法规 (EC) 第1907/2006号 / 2.符合RoHS条例 / 3.符合AFPS GS 2019:01 IPA法规 - 第2类 / 4.无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)