

fitt multiflex pu wire



适用于重型工况的抗静电管道，
传输耐磨材料的理想选择。

FITT Multiflex PU Wire配备了铜丝接地线，
确保抗静电性能，适用于建筑、工业和船舶等各种
中重型用途。

非常耐用，是运输喷砂的理想选择。

结构：带有聚氨酯内层和覆铜导电丝
(经聚氨酯包覆)的PVC螺旋管，具有抗静电性能。

使用温度：-20°C / +60°C

- 极强的内部耐磨性。
- 抗化学侵蚀能力强
- 抗压强度高。
- 良好的柔韧性。
- 防静电。
- 良好的外部耐磨性。

**Heavy-duty antistatic hose ideal for the flow of
abrasive materials.**

Fitted with copper earthing wire, which
guarantees antistatic properties, FITT Multiflex
PU Wire is suitable for all medium-heavy-duty
applications in the construction, industrial and
marine sectors. Very resistant and ideal for
sandblasting.

Structure: PVC spiral hose and PU inner layer,
with antistatic properties thanks to the PU-coated
conductive copper filament.

Temperature of use: -20°C / +60°C

- High internal abrasion resistance.
- High chemical aggression resistance.
- High crushing resistance.
- Good flexibility.
- Antistatic.
- Good external abrasion resistance.



符合REACH¹
标准
REACH¹
compliant



符合RoHS²
标准
RoHS²
compliant



无IPA³
PAH³
free



无邻苯二甲酸盐⁴
含量<0.1%
Phthalate free⁴
formulation <0.1%

FITT MULTIFLEX PU WIRE

标记 | Marking: FITT MULTIFLEX PU WIRE Øxx - PHTHALATE FREE - MADE IN ITALY

英寸 Inches [inc]	内径 Ø internal [mm]	外径 Ø external [mm]	厚度 Thickness [mm]	工作压力 Working pressure [bar]	爆破压力 Bursting pressure [bar]	真空度 Vacuum [mH ₂ O]	弯曲半径 Bending radius [mm]	长度 Length [m]	标称重量 Weight per meter [g/m]	每托盘 件数 Pieces per pallet [pcs]	托盘尺寸 Pallet dimension [cm]
2"	51	62	5,5	6	18	9	220	50	1140	3	120x120
3"	76	88	6	5	15	9	300	50	1805	3	120x120
4"	102	117,4	7,7	5	15	9	400	30	2950	3	160x160

时的爆破压力和工作压力23°C | Working and Bursting pressure at 23°C

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1. 符合REACH法规 (EC) 第1907/2006号 / 2. 符合RoHS条例 / 3. 符合AFPS GS 2019:01 IPA法规 - 第2类 / 4. 无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)