

fitt refittex 80bar



适用于农业用水和肥料输送的管道, 可承受高达80bar的压力。

FITT Refittex 80bar软管是喷雾器的理想选择, 适用于输送杀菌剂、杀虫剂和肥料溶液以及高压喷洒。也可用于清洁工作和运输压缩空气。

结构: 高强度双层聚酯增强的PVC软管。

使用温度: -20°C / +60°C

- 良好的柔性。
- 良好的外部耐磨性。
- 良好的抗化学侵蚀能力。

Hose for use with water and fertilisers in agriculture; for pressures up to 80bar.

Ideal for sprayers, FITT Refittex 80bar is suitable for the flow of fungicide solutions, pesticides and fertilisers, and for high-pressure spraying. It can also be used for cleaning applications and with compressed air.

Structure: PVC hose with double polyester reinforcement.

Temperature of use: -20°C / +60°C

- Good flexibility.
- Good external abrasion resistance.
- Good chemical aggression resistance.

REACH COMPLIANT	RoHS COMPLIANT	PAH FREE	
符合REACH ¹ 标准	符合RoHS ² 标准	无IPA ³ PAH ³ free	无邻苯二甲酸盐 ⁴ 含量<0.1%
REACH ¹ compliant	RoHS ² compliant		Phthalate free ⁴ formulation <0.1%

FITT REFITTEX 80bar

标记 | Marking: FITT REFITTEX DlxDE WP 80bar/1160psi @23°C - MADE IN ITALY

英寸 Inches [inc]	内径 Ø int. [mm]	外径 Ø ex. [mm]	颜色 Color	厚度 Thickness [mm]	工作压力 Working pressure [bar]	爆破压力 Bursting pressure [bar]	弯曲半径 Bending radius [mm]	长度 Length [m]	标称重量 Weight per meter [g/m]	每托盘 件数 Pieces per pallet [pcs]	托盘尺寸 Pallet dimension [cm]
1/3"	8	15	●	3,5	80	240	27	50	160	36	80x120
1/3"	8	15	● ●	3,5	80	240	27	100	160	20	80x120
3/8"	10	18	●	4	80	240	40	50	222	36	80x120
3/8"	10	18	●	4	80	240	40	100	222	12	80x120
1/2"	13	23	●	5	80	240	50	50	357	20	80x120
1/2"	13	23	●	5	80	240	50	100	357	8	80x120

时的爆破压力和工作压力23°C | Working and Bursting pressure at 23°C

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1.符合REACH法规 (EC) 第1907/2006号 / 2.符合RoHS条例 / 3.符合AFPS GS 2019:01 IPA法规 - 第2类 / 4.无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)