

fitt refittex cristallo



适用于食品工业、农业、工业生产设备、航海和风电领域的压力运输管道。

FITT Refittex Cristallo通过食品物质认证,可输送酒精含量高达50%vol的物质,同时也适用于压力输送空气和冷却水。在热成型工艺中,它也适用于树脂输送。

结构:高韧性聚酯纤维增强的PVC软管。

使用温度:-20°C / +60°C

- 良好的柔韧性。
- 通用性高。

Hose ideal for pressurized use in the food sector, agriculture, industrial production plants, marine and wind power sectors.

Certified for the flow of food substances with alcohol content up to 50% vol, FITT Refittex Cristallo is also ideal for use with air and cooling water. Also suitable for the flow of resins in thermoforming processes.

Structure: PVC hose with high tenacity polyester reinforcement.

Temperature of use: -20°C / +60°C

- Good flexibility.
- High level of versatility



符合REACH¹
标准
REACH¹
compliant



符合RoHS²
标准
RoHS²
compliant



无IPA³
PAH³
free



无邻苯二甲酸盐⁴
含量<0.1%
Phthalate free⁴
formulation <0.1%



MOCA - 符合欧盟第10/2011号法规
(模拟物A-B-C-D1)
符合FDA CFR 21 - 第170至199部分第175.300条
的规定。

FCM - Compliant with European Regulation
10/2011 for Simulants A-B-C-D1.
Compliant with FDA CFR 21 - Parts 170 to 199
item 175.300.

FITT REFITTEX CRISTALLO

标记 | Marking: FITT REFITTEX CRISTALLO DlxDE Reg.(EU) 10/2011 A-B-C-D1 FDA CFR 21 175.300 - PHTHALATE FREE - MADE IN ITALY

内径 Ø internal [mm]	外径 Ø external [mm]	厚度 Thickness [mm]	工作压力 Working pressure [bar]	爆破压力 Bursting pressure [bar]	弯曲半径 Bending radius [mm]	长度 Length [m]	标称重量 Weight per meter [g/m]	每托盘件数 Pieces per pallet [pcs]	托盘尺寸 Pallet dimension [cm]
4	10	3	30	90	12	5	79	504	80x120
4	10	3	30	90	12	50	79	56	80x120
4	10	3	30	90	12	100	79	30	80x120
5	11	3	26	78	15	100	92	30	80x120
6	11	2,5	20	60	24	50	81	64	80x120
6	12	3	20	60	16	5	103	432	80x120
6	12	3	20	60	16	25	103	110	80x120
6	12	3	20	60	16	50	103	48	80x120
6	12	3	20	60	16	100	103	42	80x120
8	13	2,5	20	60	35	50	100	48	80x121
8	14	3	20	60	25	5	126	360	80x122
8	14	3	20	60	25	25	126	80	80x120
8	14	3	20	60	25	50	126	48	80x120
8	14	3	20	60	25	100	126	24	80x120
9	14	2,5	20	60	25	50	110	48	80x120
9	15	3	20	60	31	100	138	24	80x120
9	15	3	20	60	31	50	138	36	80x120
9	15	3	20	60	31	25	138	80	80x120
10	15	2,5	20	60	45	50	120	36	80x120
10	16	3	20	60	35	5	145	288	80x120

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1.符合REACH法规 (EC) 第1907/2006号 / 2.符合RoHS条例 / 3.符合AFPS GS 2019:01 IPA法规 - 第2类 / 4.无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free(<0.1% weight/weight)