

fitt venflex pu ld



工业和燃气
INDUSTRY & GAS



在轻真空条件下抽吸研磨性粉尘的理想工业用软管。

在大直径范围内, Fitt Venflex PU LD适用于吸取含油烟雾和磨蚀性粉尘。在小直径范围内, 该螺旋管非常适合用于细粉尘的吸取, 可安装在纤维收集器和吸取臭氧的设备上。

结构: 聚酯型聚氨酯管, 配有抗冲击的硬质PVC增强螺旋。

使用温度: -40°C / +75°C

- 高柔韧性。
- 抗臭氧和抗油性物质能力高。
- 极强的内部和外部耐磨性。

Hose for industrial use, ideal for the suction of abrasive powders in light vacuum applications.

In large diameters, Fitt Venflex PU LD is suitable for suctioning abrasive dusts and oil-containing fumes. In small diameters, It's ideal for fine dust extraction, for installation on fiber collection machines and on ozone-sucking machinery.

Structure: Ester PU spiral hose with reinforcement spiral in rigid shock-resistant PVC.

Temperature of use: -40°C / +75°C

- High flexibility.
- High resistance to ozone and oily substances.
- Extreme internal and external abrasion resistance.



符合REACH¹
标准
REACH¹
compliant



符合RoHS²
标准
RoHS²
compliant



无IPA³
PAH³
free



无邻苯二甲酸盐⁴
含量<0.1%
Phthalate free⁴
formulation <0.1%

FITT VENFLEX PU LD

标记 | Marking: FITT VENFLEX PU LD Øxx - PHTHALATE FREE - MADE IN ITALY

英寸 Inches [inc]	内径 Ø internal [mm]	外径 Ø external [mm]	厚度 Thickness [mm]	真空度 Vacuum [mH ₂ O]	弯曲半径 Bending radius [mm]	长度 Length [m]	标称重量 Weight per meter [g/m]	每托盘件数 Pieces per pallet [pcs]	托盘尺寸 Pallet dimension [cm]
-	25	29,8	2,4	3	25	20	130	63	120x120
1 1/4"	32	37	2,5	3	32	20	175	24	120x120
-	35	40,2	2,6	3	35	20	190	20	120x120
1 1/2"	38	43,4	2,7	3	38	20	200	20	120x120
-	40	45,6	2,8	3	40	20	230	20	120x120
1 3/4"	45	50,8	2,9	3	45	20	270	16	120x120
2"	50	56,4	3,2	3	50	20	310	16	120x120
-	60	66,8	3,4	2	60	20	390	8	80x160
2 1/2"	63	70	3,5	2	63	20	440	8	80x160
-	70	79,4	4,7	2	70	20	458	4	120x100
3"	76	85,6	4,8	2	76	20	532	4	120x100
-	80	90,4	5,2	2	80	20	617	4	120x100
-	90	100,6	5,3	2	90	20	704	3	120x120
-	100	111	5,5	2	100	20	817	3	120x120
-	110	121,6	5,8	1	110	20	952	3	120x120
-	120	132	6	1	120	20	987	4	120x120
-	125	137,2	6,1	1	125	20	1061	3	120x120
-	130	142,6	6,3	1	130	20	1162	3	160x160
-	140	152,8	6,4	1	140	20	1238	3	160x160
-	150	163,2	6,6	1	150	20	1308	3	160x160

时的爆破压力和工作压力23°C | Working and Bursting pressure at 23°C

内径和相应公差符合现行UNI EN ISO 1307标准。长度公差为±5%。

Inner diameters and corresponding tolerances according to the current standard UNI EN ISO 1307. The length tolerance is ± 5%.

法规符合性说明: 1.符合REACH法规 (EC) 第1907/2006号 / 2.符合RoHS条例 / 3.符合AFPS GS 2019:01 IPA法规 - 第2类 / 4.无邻苯二甲酸盐 (含量<0.1%)

Regulatory compliance legend: 1. REACH Regulation (EC) n. 1907/2006 / 2. RoHS Directive / 3. AFPS GS 2019:01 Regulation IPA - Category 2 / 4. Phthalate free (<0.1% weight/weight)